



Iranian Journal of Physics Research, Vol. 21, No. 2, 2021
DOI: 10.47176/ijpr.21.2.38361

Effect of dye absorption time on performance of ZnO, TiO₂ and SnO₂ nanoparticle photo-anodes in dye sensitized solar cell

A Arabkhorasani, E Saievar-Iranizad, and A Bayat

Department of Physics, Tarbiat Modares University, Tehran, Iran
E-mail: saievare@modares.ac.ir

(Received 11 July 2020 ; in final form 13 February 2021)

Abstract

Interior design, engineering, and the configuration of materials used in photo-anode systems play key roles in the photovoltaic performance of dye solar cells. In this study, the photo-anodes of dye sensitized solar cells were fabricated based on TiO₂, ZnO and SnO₂ nanoparticles separately using doctor Blade method on the transparent conductive oxide as substrates, then sensitized with N719 dye. Due to the fact that the dye plays the role of photon absorption, different photo-anode oxides were placed in a N719 dye solution over a different time period. Based on current-voltage curve, efficiency parameter, short-circuit current density, open circuit voltage, and fill factor of the cells were obtained. The results of current-voltage characterization indicate that the best time for the N719 dye loading for the TiO₂ and SnO₂ layers is 20 h and for the ZnO layer is 1 h.

Keywords: solar cell, titanium dioxide, zinc oxide, tin dioxide, sensitizing time

For full article, refer to the Persian section